



A	<p>Current Rating: 3 Amps          Insulator Resistance: 1000 Megohms min          Dielectric Withstanding: AC 500V          Contact Resistance: 20mΩ MAX          Operation Temperature: -40~+105°C          Max processing temp: 230°C for 60seconds          Max processing temp: 260°C for 10seconds          Contact Material: Brass          Insulator material: Standard: Polyester, UL 94V-0</p>
B	<p>Standard: PA6T          Finish: Tin Gold Plated          Standard: Gold Flash all over</p>
C	<p>Recommended P.C. Board          SMD Layout</p>
D	<p>1. Insulator material: 5. Contact Plated:          A=PBT N=PA6T T=Matte Tin over Nickel          L=LCP P=PA9T W=Matte Tin over nickel 150μ" E=Gold 5μ" , Matte Tin 100μ"          2. Circuits:1-40 PIN Y=Bright Tin over Nickel G=Gold 10μ"          3. Tail Style: F= Gold Flash, Matte Tin 100μ" J=Gold 10μ" , Matte Tin 100μ"          S0=180° A=Gold 3μ" L= Gold 15μ"          4. Color: B=Gold 3μ" , Matte Tin 100μ" M=Gold 15μ" , Matte Tin 100μ"          BK=Black D= Gold 5μ" V=Gold 30μ" Matte Tin 100μ"</p> <p>6.Special Options          7. Packing:          A=Bag B=Tube          C=Tray E=Cap+Reel</p>
E	<p>H1 X 25 - 1 XX S0 BK X 000 X          1 2 3 4 5 6 7</p>
F	<p>东莞市震升电子有限公司          DONG GUAN ZHEN SHENG ELECTRONICS CO., LTD          BOM 1:H1N25-140BKHOCL          2:SQ0.64-11.5-X-C12          3:          PART NO. H1X25-1XXS0BKX000X .X .XX .XXX          DRAWING NO ZS-00150-P EDITION:A1 ±0.30 ±0.20 ±0.1          DRAWN BY Deng Jin Quan 2021-12-26 SCALE:1:1          APPROVAL BY Chen xiao guang 2021-12-28 UNIT:M:M</p>