



A	<p>Current Rating: 3 Amps Insulator Resistance: 1000 Megohms min Dielectric Withstanding: AC 500V Contact Resistance: 20mΩ MAX Operation Temperature: -40~+105°C Max processing temp: 230°C for 60seconds Max processing temp: 260°C for 10seconds Contact Material: Brass Insulator material: Standard: Polyester, UL 94V-0 Standard: PA6T</p>																														
B	<p>Finish: Tin Gold Plated Standard: Gold Flash all over</p>																														
C	<p>Recommended P.C. Board SMD Layout</p>																														
D	<p>2.54*No. of Contacts/2-2.54</p>																														
E	<p>2.54*No. of Contacts/2-2.54</p>																														
F	<table border="1"> <tr> <td colspan="2">PART NO.</td> <td>H1X25-2XXR0BKX000X</td> <td>.X</td> <td>.XX</td> <td>.XXX</td> </tr> <tr> <td colspan="2">DRAWING NO</td> <td>ZS-00154-P</td> <td>±0.30</td> <td>±0.20</td> <td>±0.1</td> </tr> <tr> <td colspan="2">DRAWN BY</td> <td>Deng jin quan</td> <td colspan="2">EDITION:A1</td> <td>ITEM: H1</td> </tr> <tr> <td colspan="2">APPROVAL BY</td> <td>Chen xiao guang</td> <td colspan="2">2022-5-25</td> <td>SCALE:1:1</td> </tr> <tr> <td colspan="2">TEL:0769-85305015 FAX:0769-85845060</td> <td colspan="2">UNIT:M.M</td> <td colspan="2"></td> </tr> </table>	PART NO.		H1X25-2XXR0BKX000X	.X	.XX	.XXX	DRAWING NO		ZS-00154-P	±0.30	±0.20	±0.1	DRAWN BY		Deng jin quan	EDITION:A1		ITEM: H1	APPROVAL BY		Chen xiao guang	2022-5-25		SCALE:1:1	TEL:0769-85305015 FAX:0769-85845060		UNIT:M.M			
PART NO.		H1X25-2XXR0BKX000X	.X	.XX	.XXX																										
DRAWING NO		ZS-00154-P	±0.30	±0.20	±0.1																										
DRAWN BY		Deng jin quan	EDITION:A1		ITEM: H1																										
APPROVAL BY		Chen xiao guang	2022-5-25		SCALE:1:1																										
TEL:0769-85305015 FAX:0769-85845060		UNIT:M.M																													

1. Insulator material: A=PBT N=PA6T L=LCP P=PA9T
 2. Circuits: 2-40 PIN
 3. Tail Style: R0=90°
 4. Color: BK=Black

5. Contact Plated: T=Matte Tin over Nickel W=Matte Tin over nickel 150μ" Y=Bright Tin over Nickel F=Gold Flash, Matte Tin 100μ" A=Gold 3μ" B=Gold 3μ" C=ordinary gold plating D=Gold 5μ"
 I=Gold 1μ" E=Gold 5μ" G=Gold 10μ" J=Gold 10μ" L=Gold 15μ" M=Gold 15μ" U=Gold 30μ" V=Gold 30μ"

6. Special Options
 7. Packing: A=Bag B=Tube C=Tray E=Cap+Reel

东莞市震升电子有限公司
 DONG GUAN ZHEN SHENG ELECTRONICS CO., LTD