



<p>1. Insulator material: A=PBT N=PA6T L=LCP P=PA9T Circuits:1-40 PIN</p> <p>2. Tail Style: SO=180° Color: BK=Black</p> <p>3. Contact Plated: T=Matte Tin over Nickel W=Matte Tin over nickel 150μ" Y=Bright Tin over Nickel F= Gold Flash, Matte Tin 100μ" A=Gold 3μ" B=Gold 3μ" C = ordinary gold plating D= Gold 5μ"</p> <p>4. Contact Plated: I= Gold 1μ" E=Gold 5μ" G=Gold 10μ" J=Gold 10μ" L= Gold 15μ" M=Gold 15μ" U= Gold 30μ" V=Gold 30μ"</p> <p>5. Contact Plated: Matte Tin 100μ" Matte Tin 100μ" Matte Tin 100μ" Matte Tin 100μ" Matte Tin 100μ" Matte Tin 100μ"</p> <p>6.Special Options</p> <p>7. Packing: A=Bag B=Tube C=Tray E=Cap+Reel</p> <p>8. (RoHS Compliant)</p> <p>H1 X 25 - 2 XX S0 BK X 000 X</p>					
<p>1. HIN25-240BKHC1</p> <p>2. S0064-11.6-X-C12</p> <p>3.</p> <p>东莞市震升电子有限公司 DONG GUAN ZHEN SHENG ELECTRONICS CO., LTD</p> <p>TEL:0769-85305015 FAX:0769-85845060</p>	<p>PART NO. H1X25-2XXS0BKX000X</p> <p>DRAWING NO. ZS-00156-P</p> <p>DRAWN BY Deng Jin Quan</p> <p>APPROVAL BY Chen xiao guang</p>	<p>Recommended P.C. Board SMD Layout</p>	<p>Current Rating: 3 Amps</p> <p>Insulator Resistance: 1000 Megohms min</p> <p>Dielectric Withstanding: AC 500V</p> <p>Contact Resistance: 20mΩ MAX</p> <p>Operation Temperature: -40~+105°C</p> <p>Max processing temp: 230°C for 60seconds</p> <p>Max processing temp: 260°C for 10seconds</p> <p>Contact Material: Brass</p> <p>Insulator material: Standard: Polyester, UL 94V-0</p> <p>Standard: PA6T</p> <p>Finish: Tin Gold Plated</p> <p>Standard: Gold Flash all over</p>	<p>Current Rating: 3 Amps</p> <p>Insulator Resistance: 1000 Megohms min</p> <p>Dielectric Withstanding: AC 500V</p> <p>Contact Resistance: 20mΩ MAX</p> <p>Operation Temperature: -40~+105°C</p> <p>Max processing temp: 230°C for 60seconds</p> <p>Max processing temp: 260°C for 10seconds</p> <p>Contact Material: Brass</p> <p>Insulator material: Standard: Polyester, UL 94V-0</p> <p>Standard: PA6T</p> <p>Finish: Tin Gold Plated</p> <p>Standard: Gold Flash all over</p>	<p>Current Rating: 3 Amps</p> <p>Insulator Resistance: 1000 Megohms min</p> <p>Dielectric Withstanding: AC 500V</p> <p>Contact Resistance: 20mΩ MAX</p> <p>Operation Temperature: -40~+105°C</p> <p>Max processing temp: 230°C for 60seconds</p> <p>Max processing temp: 260°C for 10seconds</p> <p>Contact Material: Brass</p> <p>Insulator material: Standard: Polyester, UL 94V-0</p> <p>Standard: PA6T</p> <p>Finish: Tin Gold Plated</p> <p>Standard: Gold Flash all over</p>