



Recommended P.C. Board
SMD Layout

1. Insulator material: A=PBT N=PA6T L=LCP P=PA9T
2. Circuits:1-40 PIN
3. Tail Style: S0=180°
4. Color: BK=Black

5. Contact Plated: T=Matte Tin over Nickel W=Matte Tin over nickel 150μm Y=Bright Tin over Nickel F=Gold Flash, Matte Tin 100μm A=Gold 3μm B=Gold 3μm C=ordinary gold plating D=Gold 5μm

6.Special Options: I=Gold 1μm E=Gold 5μm G=Gold 10μm J=Gold 10μm L=Gold 15μm M=Gold 15μm U=Gold 30μm V=Gold 30μm

7. Packing: A=Bag B=Tube C=Tray E=Cap+Reel

H1 X 25 - 2 XX S0 BK X D00 X



PART NO.		H1X25-2XXS0BKXD00X	
DRAWING NO		ZS-00157-P	
DRAWN BY		Deng Jin Quan	
APPROVAL BY		Chen xiao guang	

1: H1N25-240BKHC1		X	.XX	.XXX
2: SQ0.64-17.1-X-C12		±0.30	±0.20	±0.1
3:			ITEM: H1	SCALE: 1:1
TEL: 0769-85305015 FAX: 0769-85845060		UNIT: M.M		

1

2

3

4

5

6

7

8

A

B

C

D

E

F