



Current Rating: 2 Amps
Insulator Resistance: 1000 Megohms min
Dielectric Withstanding: AC 500V
Contact Resistance: 20mΩ MAX
Operation Temperature: -40~+105°C
Max processing temp: 230°C for 60seconds
Max processing temp: 260°C for 10seconds
Contact Material: Brass
Insulator material: Standard: Polyester, UL 94V-0
Standard: PA6T
Finish: Tin Gold Plated
Standard: Gold Flash all over

Recommended P.C. Board
 SMD Layout

H2 X 20 - 2 XX DS BK X D39E
 1 2 3 4 5 6 7

1. Insulator material: 5. Contact Plated:
- N=PA6T T=Matte Tin over Nickel
 - L=LCP P=PA9T W=Matte Tin over nickel 150μ"
 - 2. Circuits:2-40 PIN Y=Bright Tin over Nickel
 - 3. Tail Style: F=Gold Flash, Matte Tin 100μ"
 - D1=SMT+Pillars A=Gold 3μ"
 - 4. Color: B=Gold 3μ"
 - BK=Black D=Gold 5μ"
- 6.Special Options
- I=Gold 1μ"
 - E=Gold 5μ"
 - J=Gold 10μ"
 - L=Gold 10μ"
 - M=Gold 15μ"
 - V=Gold 30μ"
 - Matte Tin 100μ"
 - Matte Tin 100μ"
 - Matte Tin 100μ"
 - Matte Tin 100μ"
 - Matte Tin 100μ"
 - Matte Tin 100μ"
7. Packing:
- A=Bag
 - B=Tube
 - D=Small box
 - E=Cap+Reel

东莞市震升电子有限公司 DONG GUAN ZHEN SHENG ELECTRONICS CO., LTD		PART NO.		H2X20-2XXD1BKXD39E		.X		.XX		.XXX	
BOM		DRAWING NO		ZS-10120-P		±0.30		±0.20		±0.1	
1:H2N20-140BKHC1		DRAWN BY		Deng jin quan		2021-12-25		SCALE:1:1		ITEM: H2	
2:SQ005-9/15.2-X-C12		APPROVAL BY		Chen xiao guang		2021-12-27		UNIT:M.M			
3:H2N-CAP-H0-C4											
TEL:0769-85305015 FAX:0769-85845060											