



<p>1. Insulator material: N=PA6T L=LCP P=PA9T 2. Circuits: 2-40 PIN 3. Tail Style: S0=180° 4. Color: BK=Black</p> <p>5. Contact Plated: T=Matte Tin over Nickel W=Matte Tin over nickel 150μ" Y=Bright Tin over Nickel F=Gold Flash, Matte Tin 100μ" A=Gold 3μ" B=Gold 3μ" C = ordinary gold plating D = Gold 5μ"</p> <p>6.Special Options</p> <p>7. Packing: A=Bag B=Tube D=Small box E=Cap+Reel</p>	<p>H2 X 20 - 2 XX S0 BK X 000 X</p> <p>1 2 3 4 5 6 7</p>	<p>1. Insulator material: T=Gold 1μ" E=Gold 5μ" G=Gold 10μ" J=Gold 10μ" L = Gold 15μ" M=Gold 15μ" U = Gold 30μ" V=Gold 30μ"</p>	<p>Recommended P.C. Board SMD Layout</p>	<p>Current Rating: 2 Amps Insulator Resistance: 1000 Megohms min Dielectric Withstanding: AC 500V Contact Resistance: 20mΩ MAX Operation Temperature: -40~+105°C Max processing temp: 230°C for 60seconds Max processing temp: 260°C for 10seconds Contact Material: Brass Insulator material: Standard: Polyester, UL 94V-0 Standard: PA6T</p> <p>Finish: Tin Gold Plated Standard: Gold Flash all over</p>	<p>2.0*No.of Contacts/2±0.30</p>	<p>2.00</p>	<p>2.00</p>	<p>2.00</p>
<p>1. Insulator material: N=PA6T L=LCP P=PA9T 2. Circuits: 2-40 PIN 3. Tail Style: S0=180° 4. Color: BK=Black</p> <p>5. Contact Plated: T=Matte Tin over Nickel W=Matte Tin over nickel 150μ" Y=Bright Tin over Nickel F=Gold Flash, Matte Tin 100μ" A=Gold 3μ" B=Gold 3μ" C = ordinary gold plating D = Gold 5μ"</p> <p>6.Special Options</p> <p>7. Packing: A=Bag B=Tube D=Small box E=Cap+Reel</p>	<p>H2 X 20 - 2 XX S0 BK X 000 X</p> <p>1 2 3 4 5 6 7</p>	<p>1. Insulator material: T=Gold 1μ" E=Gold 5μ" G=Gold 10μ" J=Gold 10μ" L = Gold 15μ" M=Gold 15μ" U = Gold 30μ" V=Gold 30μ"</p>	<p>Recommended P.C. Board SMD Layout</p>	<p>Current Rating: 2 Amps Insulator Resistance: 1000 Megohms min Dielectric Withstanding: AC 500V Contact Resistance: 20mΩ MAX Operation Temperature: -40~+105°C Max processing temp: 230°C for 60seconds Max processing temp: 260°C for 10seconds Contact Material: Brass Insulator material: Standard: Polyester, UL 94V-0 Standard: PA6T</p> <p>Finish: Tin Gold Plated Standard: Gold Flash all over</p>	<p>2.0*No.of Contacts/2±0.30</p>	<p>2.00</p>	<p>2.00</p>	<p>2.00</p>
<p>1. Insulator material: N=PA6T L=LCP P=PA9T 2. Circuits: 2-40 PIN 3. Tail Style: S0=180° 4. Color: BK=Black</p> <p>5. Contact Plated: T=Matte Tin over Nickel W=Matte Tin over nickel 150μ" Y=Bright Tin over Nickel F=Gold Flash, Matte Tin 100μ" A=Gold 3μ" B=Gold 3μ" C = ordinary gold plating D = Gold 5μ"</p> <p>6.Special Options</p> <p>7. Packing: A=Bag B=Tube D=Small box E=Cap+Reel</p>	<p>H2 X 20 - 2 XX S0 BK X 000 X</p> <p>1 2 3 4 5 6 7</p>	<p>1. Insulator material: T=Gold 1μ" E=Gold 5μ" G=Gold 10μ" J=Gold 10μ" L = Gold 15μ" M=Gold 15μ" U = Gold 30μ" V=Gold 30μ"</p>	<p>Recommended P.C. Board SMD Layout</p>	<p>Current Rating: 2 Amps Insulator Resistance: 1000 Megohms min Dielectric Withstanding: AC 500V Contact Resistance: 20mΩ MAX Operation Temperature: -40~+105°C Max processing temp: 230°C for 60seconds Max processing temp: 260°C for 10seconds Contact Material: Brass Insulator material: Standard: Polyester, UL 94V-0 Standard: PA6T</p> <p>Finish: Tin Gold Plated Standard: Gold Flash all over</p>	<p>2.0*No.of Contacts/2±0.30</p>	<p>2.00</p>	<p>2.00</p>	<p>2.00</p>

<p>1. Insulator material: N=PA6T L=LCP P=PA9T 2. Circuits: 2-40 PIN 3. Tail Style: S0=180° 4. Color: BK=Black</p> <p>5. Contact Plated: T=Matte Tin over Nickel W=Matte Tin over nickel 150μ" Y=Bright Tin over Nickel F=Gold Flash, Matte Tin 100μ" A=Gold 3μ" B=Gold 3μ" C = ordinary gold plating D = Gold 5μ"</p> <p>6.Special Options</p> <p>7. Packing: A=Bag B=Tube D=Small box E=Cap+Reel</p>	<p>H2 X 20 - 2 XX S0 BK X 000 X</p> <p>1 2 3 4 5 6 7</p>	<p>1. Insulator material: T=Gold 1μ" E=Gold 5μ" G=Gold 10μ" J=Gold 10μ" L = Gold 15μ" M=Gold 15μ" U = Gold 30μ" V=Gold 30μ"</p>	<p>Recommended P.C. Board SMD Layout</p>	<p>Current Rating: 2 Amps Insulator Resistance: 1000 Megohms min Dielectric Withstanding: AC 500V Contact Resistance: 20mΩ MAX Operation Temperature: -40~+105°C Max processing temp: 230°C for 60seconds Max processing temp: 260°C for 10seconds Contact Material: Brass Insulator material: Standard: Polyester, UL 94V-0 Standard: PA6T</p> <p>Finish: Tin Gold Plated Standard: Gold Flash all over</p>	<p>2.0*No.of Contacts/2±0.30</p>	<p>2.00</p>	<p>2.00</p>	<p>2.00</p>
---	--	---	--	--	----------------------------------	-------------	-------------	-------------

<p>1. Insulator material: N=PA6T L=LCP P=PA9T 2. Circuits: 2-40 PIN 3. Tail Style: S0=180° 4. Color: BK=Black</p> <p>5. Contact Plated: T=Matte Tin over Nickel W=Matte Tin over nickel 150μ" Y=Bright Tin over Nickel F=Gold Flash, Matte Tin 100μ" A=Gold 3μ" B=Gold 3μ" C = ordinary gold plating D = Gold 5μ"</p> <p>6.Special Options</p> <p>7. Packing: A=Bag B=Tube D=Small box E=Cap+Reel</p>	<p>H2 X 20 - 2 XX S0 BK X 000 X</p> <p>1 2 3 4 5 6 7</p>	<p>1. Insulator material: T=Gold 1μ" E=Gold 5μ" G=Gold 10μ" J=Gold 10μ" L = Gold 15μ" M=Gold 15μ" U = Gold 30μ" V=Gold 30μ"</p>	<p>Recommended P.C. Board SMD Layout</p>	<p>Current Rating: 2 Amps Insulator Resistance: 1000 Megohms min Dielectric Withstanding: AC 500V Contact Resistance: 20mΩ MAX Operation Temperature: -40~+105°C Max processing temp: 230°C for 60seconds Max processing temp: 260°C for 10seconds Contact Material: Brass Insulator material: Standard: Polyester, UL 94V-0 Standard: PA6T</p> <p>Finish: Tin Gold Plated Standard: Gold Flash all over</p>	<p>2.0*No.of Contacts/2±0.30</p>	<p>2.00</p>	<p>2.00</p>	<p>2.00</p>
---	--	---	--	--	----------------------------------	-------------	-------------	-------------