



<p>1. Insulator material: N=PA6T L=LCP P=PA9T 2. Circuits: 2-40 PIN 3. Tail Style: S0=180° 4. Color: BK=Black</p> <p>5. Contact Plated: T=Matte Tin over Nickel W=Matte Tin over nickel Y=Bright Tin over Nickel F=Gold Flash, Matte Tin 100µ" A=Gold 3µ" B=Gold 3µ" C = ordinary gold plating D=Gold 5µ"</p> <p>6. Special Options</p> <p>7. Packing: A=Bag B=Tube C=Small box D=Cap+Reel</p>	<p>H2 X 20 - 2 XX S0 BK X D00 X</p> <p>1 2 3 4 5 6 7</p>	<p>1: H2N20-240BKHC1 2: SQ0.5-11.7-X-C12 3:</p>	<p>1: H2N20-240BKHC1 2: SQ0.5-11.7-X-C12 3:</p>	<p>1: H2N20-240BKHC1 2: SQ0.5-11.7-X-C12 3:</p>	<p>1: H2N20-240BKHC1 2: SQ0.5-11.7-X-C12 3:</p>
<p>1. Insulator material: N=PA6T L=LCP P=PA9T 2. Circuits: 2-40 PIN 3. Tail Style: S0=180° 4. Color: BK=Black</p> <p>5. Contact Plated: T=Matte Tin over Nickel W=Matte Tin over nickel Y=Bright Tin over Nickel F=Gold Flash, Matte Tin 100µ" A=Gold 3µ" B=Gold 3µ" C = ordinary gold plating D=Gold 5µ"</p> <p>6. Special Options</p> <p>7. Packing: A=Bag B=Tube C=Small box D=Cap+Reel</p>	<p>H2 X 20 - 2 XX S0 BK X D00 X</p> <p>1 2 3 4 5 6 7</p>	<p>1: H2N20-240BKHC1 2: SQ0.5-11.7-X-C12 3:</p>	<p>1: H2N20-240BKHC1 2: SQ0.5-11.7-X-C12 3:</p>	<p>1: H2N20-240BKHC1 2: SQ0.5-11.7-X-C12 3:</p>	<p>1: H2N20-240BKHC1 2: SQ0.5-11.7-X-C12 3:</p>

Current Rating: 2 Amps
 Insulator Resistance: 1000 Megohms min
 Dielectric Withstanding: AC 500V
 Contact Resistance: 20mΩ MAX
 Operation Temperature: -40~+105°C
 Max processing temp: 230°C for 60seconds
 Max processing temp: 260°C for 10seconds
 Contact Material: Brass
 Insulator material: Standard: Polyester, UL 94V-0
 Standard: PA6T
 Finish: Tin Gold Plated
 Standard: Gold Flash all over

Recommended P.C. Board
SMD Layout

<p>东莞市震升电子有限公司 DONG GUAN ZHEN SHENG ELECTRONICS CO., LTD</p>	<p>PART NO. H2X20-2XXS0BKXD00X</p>	<p>DRAWING NO. ZS-00106-P</p>	<p>EDITION: A1</p>
<p>BOM 1: H2N20-240BKHC1</p>	<p>DRAWN BY Deng jin quan</p>	<p>2021-12-25</p>	<p>SCALE: 1:1</p>
<p>TEL: 0769-85305015 FAX: 0769-85845060</p>	<p>APPROVAL BY Chen xiao guang</p>	<p>2021-12-27</p>	<p>UNIT: M.M</p>