



Current Rating: 2 Amps
Insulator Resistance: 1000 Megohms min
Dielectric Withstanding: AC 500V
Contact Resistance: 20mΩ MAX
Operation Temperature: -40~+105°C
Max processing temp: 230°C for 60seconds
Max processing temp: 260°C for 10seconds
Contact Material: Brass
Insulator material: Standard: Polyester, UL 94V-0
Standard: PA6T
Finish: Tin Gold Plated
Standard: Gold Flash all over

<p>东莞市震升电子有限公司 DONG GUAN ZHEN SHENG ELECTRONICS CO., LTD</p>		PART NO. H2X20-3XXS0BKX000X X ±0.30 XX ±0.20 XXX ±0.1	
BOM 1: H2N20-340BKHOCL 2: S00 5-8-8-X-C12 3:		DRAWING NO ZS-10046-P EDITION: A1 ITEM: H2	
TEL: 0769-85305015 FAX: 0769-85845060		DRAWN BY Deng jin quan SCALE: 1:1	
APPROVAL BY Chen xiao guang		2021-12-27 UNIT: M:M	

1. Insulator material: 5. Contact Plated:
 N=PA6T T=Matte Tin over Nickel I=Gold 1μ"
 L=LCP P=PA9T W=Matte Tin over nickel 150μ" E=Gold 5μ"
 2. Circuits: 2-40 PIN Y=Bright Tin over Nickel G=Gold 10μ"
 3. Tail Style: F=Gold Flash, Matte Tin 100μ" J=Gold 10μ"
 S0=180° A=Gold 3μ" L=Gold 15μ"
 4. Color: B=Gold 3μ" M=Gold 15μ"
 BK=Black D=Gold 5μ" V=Gold 30μ"

6. Special Options
7. Packing:
 A=Bag B=Tube
 D=Small box E=Cap+Reel

1. Insulator material: 5. Contact Plated:
 T=Matte Tin over Nickel I=Gold 1μ"
 W=Matte Tin over nickel 150μ" E=Gold 5μ"
 Y=Bright Tin over Nickel G=Gold 10μ"
 F=Gold Flash, Matte Tin 100μ" J=Gold 10μ"
 A=Gold 3μ" L=Gold 15μ"
 B=Gold 3μ" M=Gold 15μ"
 C = ordinary gold plating U=Gold 30μ"
 D=Gold 5μ" V=Gold 30μ"

(RoHS Compliant)
 H2 X 20 - 3 XX S0 BK X 029 X
 1 2 3 4 5 6 7

1 **2** **3** **4** **5** **6** **7** **8**