



Current Rating: 1 Amps
Insulator Resistance: 1000 Megohms min
Dielectric Withstanding: AC 300V
Contact Resistance: 20mΩ MAX
Operation Temperature: -40~+105°C
Max processing temp: 230°C for 60seconds
Max processing temp: 260°C for 10seconds
Contact Material: Brass
Insulator material: Standard: Polyester, UL 94V-0
Standard: PA6T
Finish: Tin Gold Plated
Standard: Gold Flash all over

(RoHS Compliant)
H3 X 15 - 1 XX R0 BK X 000 X
 1 2 3 4 5 6 7

- 1. Insulator material:**
- N=PA6T
 - L=LCP P=PA9T
 - 2. Circuits:2-50 PIN
 - 3. Tail Style:
 - R0=Right angle
 - 4. Color: BK=Black
- 5. Contact Plated:**
- T=Matte Tin over Nickel
 - W=Matte Tin over nickel 150μ"
 - Y=Bright Tin over Nickel
 - F=Gold Flash, Matte Tin 100μ"
 - A=Gold 3μ"
 - B=Gold 3μ"
 - C = ordinary gold plating
 - D = Gold 5μ"
- 6.Special Options**
- I= Gold 1μ"
 - E=Gold 5μ"
 - G=Gold 10μ"
 - J=Gold 10μ"
 - L = Gold 15μ"
 - M=Gold 15μ"
 - U = Gold 30μ"
 - V=Gold 30μ"
- 7. Packing:**
- A=Bag
 - B=Tube
 - D=Small box
 - E=Cap+Reel

<p>东莞市震升电子有限公司 DONG GUAN ZHEN SHENG ELECTRONICS CO., LTD</p>		PART NO.		H3X15-1XXR0BKX000X		.X		.XX		.XXX	
1: H3N15-150BKHC4		DRAWING NO		ZS-00034-P		±0.30		±0.20		±0.1	
BOM 2: SQ0.4-8.7-X-C12		DRAWN BY		Deng jin quan		2021-12-25		SCALE: 1:1		ITEM: H3	
3:		APPROVAL BY		Chen xiao guang		2021-12-27		UNIT: M.M			

TEL: 0769-85305015 FAX: 0769-85845060