



1	2	3	4	5	6	7	8
---	---	---	---	---	---	---	---

(RoHS Compliant)

H3 X 20 - 2 XX R0 BK X D30 X

1. Insulator material: 5. Contact Plated:

N=PA6T T=Matte Tin over Nickel
 L=LCP P=PA9T W=Matte Tin over nickel
 2. Circuits:2-50 PIN Y=Bright Tin over Nickel
 3. Tail Style: F=Gold Flash, Matte Tin 100μ"
 R0=Right angle A=Gold 3μ"
 4. Color: B=Gold 3μ", Matte Tin 100μ"
 BK=Black C = ordinary gold plating U = Gold 30μ"
 D = Gold 5μ" V=Gold 30μ" Matte Tin 100μ"

6.Special Options

7. Packing: I=Gold 1μ"
 E=Gold 5μ", Matte Tin 100μ"
 A=Bag G=Gold 10μ"
 B=Tube J=Gold 10μ", Matte Tin 100μ"
 D=Small box L=Gold 15μ"
 E=Cap+Reel M=Gold 15μ", Matte Tin 100μ"
 V=Gold 30μ" Matte Tin 100μ"

Recommended P.C. Board
SMD Layout

1.27*No.of Contacts/2-1.27

1.27

∅0.70

1.27

<p>Current Rating: 1 Amps</p> <p>Insulator Resistance: 1000 Megohms min</p> <p>Dielectric Withstanding: AC 300V</p> <p>Contact Resistance: 20mΩ MAX</p> <p>Operation Temperature: -40~+105°C</p> <p>Max processing temp: 230°C for 60seconds</p> <p>Max processing temp: 260°C for 10seconds</p> <p>Contact Material: Brass</p> <p>Insulator material: Standard: Polyester,UL 94V-0</p> <p>Standard: PA6T</p> <p>Finish: Tin Gold Plated</p> <p>Standard: Gold Flash all over</p>		<p>1 Amps</p> <p>1000 Megohms min</p> <p>AC 300V</p> <p>20mΩ MAX</p> <p>-40~+105°C</p> <p>230°C for 60seconds</p> <p>260°C for 10seconds</p> <p>Brass</p> <p>Standard: Polyester,UL 94V-0</p> <p>Standard: PA6T</p> <p>Tin Gold Plated</p> <p>Gold Flash all over</p>	
<p>1. H3N20-250BKHC1</p> <p>2. SQ0.4-12/14.5-X-C12</p> <p>3:</p>		<p>PART NO. H3X20-2XXR0BKXD30X</p> <p>DRAWING NO. ZS-10168-P</p> <p>DRAWN BY Deng jin quan</p> <p>APPROVAL BY Chen xiao guang</p>	
<p>东莞市震升电子有限公司</p> <p>DONG GUAN ZHEN SHENG ELECTRONICS CO., LTD</p> <p>TEL:0769-85305015 FAX:0769-85845060</p>		<p>X ±0.30</p> <p>.XX ±0.20</p> <p>.XXX ±0.1</p> <p>ITEM: H3</p> <p>SCALE:1:1</p> <p>UNIT:M.M</p>	