



A	<p>Current Rating: 1 Amps Insulator Resistance: 1000 Megohms min Dielectric Withstanding: AC 300V Contact Resistance: 20mΩ MAX Operation Temperature: -40~+105°C Max processing temp: 230°C for 60seconds Max processing temp: 260°C for 10seconds Contact Material: Brass Insulator material: Standard: Polyester, UL 94V-0 Standard: PA6T</p>
B	<p>Finish: Tin Gold Plated Standard: Gold Flash all over</p>
C	<p>Recommended P.C. Board SMD Layout</p>
D	<p>1. Insulator material: N=PA6T, L=LCP, P=PA9T, Circuits:2-50 PIN, Tail Style: S0=180°, Color: BK=Black</p> <p>2. Contact Plated: T=Matte Tin over Nickel, W=Matte Tin over nickel 150μ", Y=Bright Tin over Nickel, F=Gold Flash, Matte Tin 100μ", A=Gold 3μ", S0=180°, Matte Tin 100μ", D=Gold 5μ"</p> <p>3. Contact Plated: I=Gold 1μ", E=Gold 5μ", Matte Tin 100μ", G=Gold 10μ", J=Gold 10μ", Matte Tin 100μ", L=Gold 15μ", M=Gold 15μ", Matte Tin 100μ", U=Gold 30μ", Matte Tin 100μ", V=Gold 30μ"</p> <p>4. Special Options: 7. Packing: A=Bag, B=Tube, D=Small box, E=Cap+Reel</p>
E	<p>1. Insulator material: N=PA6T, L=LCP, P=PA9T, Circuits:2-50 PIN, Tail Style: S0=180°, Color: BK=Black</p> <p>2. Contact Plated: T=Matte Tin over Nickel, W=Matte Tin over nickel 150μ", Y=Bright Tin over Nickel, F=Gold Flash, Matte Tin 100μ", A=Gold 3μ", S0=180°, Matte Tin 100μ", D=Gold 5μ"</p> <p>3. Contact Plated: I=Gold 1μ", E=Gold 5μ", Matte Tin 100μ", G=Gold 10μ", J=Gold 10μ", Matte Tin 100μ", L=Gold 15μ", M=Gold 15μ", Matte Tin 100μ", U=Gold 30μ", Matte Tin 100μ", V=Gold 30μ"</p> <p>4. Special Options: 7. Packing: A=Bag, B=Tube, D=Small box, E=Cap+Reel</p>
F	<p>1. Insulator material: N=PA6T, L=LCP, P=PA9T, Circuits:2-50 PIN, Tail Style: S0=180°, Color: BK=Black</p> <p>2. Contact Plated: T=Matte Tin over Nickel, W=Matte Tin over nickel 150μ", Y=Bright Tin over Nickel, F=Gold Flash, Matte Tin 100μ", A=Gold 3μ", S0=180°, Matte Tin 100μ", D=Gold 5μ"</p> <p>3. Contact Plated: I=Gold 1μ", E=Gold 5μ", Matte Tin 100μ", G=Gold 10μ", J=Gold 10μ", Matte Tin 100μ", L=Gold 15μ", M=Gold 15μ", Matte Tin 100μ", U=Gold 30μ", Matte Tin 100μ", V=Gold 30μ"</p> <p>4. Special Options: 7. Packing: A=Bag, B=Tube, D=Small box, E=Cap+Reel</p>

1	2	3	4	5	6	7	8
---	---	---	---	---	---	---	---

H3 X 20 - 2 XX S0 BK X D00 X	1	2	3	4	5	6	7	8
------------------------------	---	---	---	---	---	---	---	---

PART NO.	H3X20-2XXS0BKXD00X	.X	.XX	.XXX
DRAWING NO	ZS-00067-P	±0.30	±0.20	±0.1
DRAWN BY	Deng jin quan	2021-12-25	2021-12-25	SCALE:1:1
APPROVAL BY	Chen xiao guang	2021-12-27	2021-12-27	UNIT:M.M

1. H3N20-150BKHC4	2. SQ0.4-74-X-C12	3.
-------------------	-------------------	----

TEL:0769-85305015	FAX:0769-85845060
-------------------	-------------------

东莞市震升电子有限公司	DONG GUAN ZHEN SHENG ELECTRONICS CO., LTD
-------------	---